



Datasheet



Desktop Solutions

- Class leading speed printing increases efficiency and productivity.
- Ease of use and maintenance.
- Reduced downtime as a result of high reliability.
- Compliant with ENERGY STAR®.

> B-FV4T



Printing Solutions.

TOSHIBA
Leading Innovation >>>

> B-FV4T



<p>General</p>	<p>Printing Technology Thermal Print Head Type Interface</p> <p>Thermal transfer, Direct thermal Flat GS12/TS12 model: USB 2.0, Ethernet 10/100 BaseT GS14/TS14 model: USB 2.0, Ethernet 10/100 BaseT, Serial GS16/TS16 model: USB 2.0, Parallel 32 MB (Flash ROM), 16 MB (SD-RAM) Central Top opening Reflective, Transmissive Status indicator Feed 220 x 279 x 182 mm 2.4 kg 500 labels/day</p> <p>Memory Alignment Base Media Loading Sensor User Interface Operator Keys Dimensions (W x D x H) Weight Duty Cycle²⁾</p>
<p>Print</p>	<p>Print Width 4.25 inches (108 mm) 203 dpi, 4.16 inches (105.7 mm) 300 dpi Print Speed Up to 6 ips (152.4 mm/sec) 203 dpi, Up to 4 ips (101.6 mm/sec) 300 dpi Resolution 203 dpi, 300 dpi Fonts Bitmap Print Length Max. 997 mm (203 dpi), Max. 455.2 mm (300 dpi) Barcodes EAN8, EAN13, UPC-A, UPC-E, NW-7, CODE 39, CODE 93, ITF, MSI, CODE128, EAN128, Industrial 2 of 5, POSTNET, RM4SCC, KIX CODE, USPS Intelligent mail barcode, GS1 DataBar 2D Codes Data Matrix, PDF417, QR Code, Maxi Code, Micro PDF417</p>
<p>Media</p>	<p>Media Width 22.4-118 mm Media Thickness 0.06-0.19 mm Max. Outer Roller Diameter 127 mm, 203 mm¹⁾ Core Diameter 25.4-38.1 mm, 76.2 mm¹⁾</p>
<p>Ribbon</p>	<p>Max. Ribbon Roll Diameter 40 mm Standard Ribbon Length 300 mm, 100 mm Ribbon Width 40-110 mm</p>
<p>Functions</p>	<p>Print Functions ZPL, EPL³⁾, DPL³⁾, IPL (203 dpi only)³⁾ Emulation Programming Language TPCL, BCI Issue Mode Batch, Auto cut¹⁾, Peel-off¹⁾ System Features BarTender UltraLite</p>
<p>Note: Only GS14/TS14 model available as stock item!</p>	

OPTIONS

FULL CUTTER

B-FV204T-F-QM-R

PARTIAL CUTTER

B-FV204T-P-QM-R

PEEL-OFF MODULE

B-FV904T-H-QM-R

EXTERNAL 8" OD MEDIA STAND

B-FV904-PH-QM-R

WIRELESS LAN I/F (802.11 B/G)³⁾

B-FV700-WLAN-QM-R

BLUETOOTH I/F (V2.1 + EDR)³⁾

B-FV700-BLTH-QM-R

203 DPI THERMAL PRINT HEAD

B-FV704T-TPH2-QM-R

300 DPI THERMAL PRINT HEAD

B-FV704T-TPH3-QM-R

SOLUTIONS

BarTender Software



¹⁾ Optional

²⁾ GUIDE to the no. of 4" high labels a day a printer may produce. This is neither a guarantee, nor a limitation of performance.

³⁾ Planned for future development